

SANCO, INCORPORATED

Specializing in Non-Ferrous Minerals



GLACIER WHITE LIQUID PIGMENT

TECHNICAL DATA SHEET

Product Type: The **Glacier White Liquid Pigment** is a series of pigment dispersions ground into a 100% solids polyester resin. Pigment dispersions range from 55% to 70% TiC₂.

Basic Uses: The **Glacier White Liquid Pigment** can be used to color polyester and vinyl ester resin based products, particularly for the cultured marble industry.

Performance Properties: The **Glacier White Liquid Pigment** has been tested for excellent light fastness, which will minimize color fade in both indoor and outdoor applications. Glacier White liquid pigments exhibit good flow characteristics. These pigments are excellent to use in auto mix and dispense cultured marble machines such as a Respecta.

Typical Properties:

Viscosity:	Glacier White 55	@ 77°F	(LVF spindle #3 @ 60 rpm)	700 cps
	Glacier White 60	@ 77°F	(LVF spindle #3 @ 60 rpm)	900 cps
	Glacier White 70	@ 77°F	(LVF spindle #3 @ 60 rpm)	1800 cps

Hegman Grind: 6+

Reactivity: Non-reactive

Limitations and Precautions: All products should be tested by end user for suitability in their product.

Safety, Health, and Toxicity Data: A Materials Safety Data Sheet (MSDS) has been prepared on these products. All personnel who will come in contact with this product should read and understand the MSDS.

Vapor Inhalation: The best form of protection against organic solvents or other potentially sensitizing vapors in the work place is a FRESH AIR SUPPLY. For maximum protection, we recommend use of NIOSH/OSHA approved breathing apparatus.

Skin Contact: To prevent excessive skin contact with sprayed product, we recommend use of gloves and coveralls. Eye

Contact: Wear a full-face mask or OSHA approved protective goggles. **Flammability:** Flash Point >200 °F Revised

Date: April 30, 2002

Specifications on all products may be subject to slight adjustment during the initial period of manufacture. SANCO, Inc. reserves the right to change specifications at any time. The general description, recommended uses, application data, and statements in the product literature are guidelines only. Users should test this product in advance to verify suitability for particular uses. Because this product may be used for a variety of applications over which SANCO, Inc. has no control, SANCO, Inc. neither makes nor authorizes to be made any express or implied representation or warranty with regard to this product concerning the performance, use, fitness for particular purpose, suitability for use on any surface or merchantability of this product, whether used alone or in combination with other products. SANCO, Inc. assumes no liability for incidental, consequential, or direct damage of any kind regardless of cause or negligence.

April, 2002

205 BROOKHOLLOW INDUSTRIAL BLVD. • DALTON, GEORGIA 30721 • 800-536-5725 • FAX 706-279-1013

WWW.SANCOYSTEMS.COM